

#### General

| Product number | 22501020                             |
|----------------|--------------------------------------|
| Product name   | HSAJET® MCX 1.0" Printer (2 pens) SC |
| Manufacturer   | HSA Systems A/S                      |

### **Printing Features**

| Technology          | HP TIJ 2.5 w. smart card technology  |
|---------------------|--|
| Print distance      | 0.5-5.0 mm (from nozzle to surface)  |
| Print height        | Up to 25.4 mm (1") (2 pens)  |
| Max length          | 4 m @ 200 dpi   2.7 m @ 300 dpi  |
| Frequency           | 18 kHz   |
| Resolution          | Horizontal: from 100 to 2400 dpi (variable dpi)<br>Vertical: 300 or 600 dpi                      |
| Smart card features | Automatic detection of ink cartridge, auto-adjustment of ink parameters, monitoring of ink level |
| Encoder rollback    | Detection of print position enabling restart of print in correct position                        |
|                     |  |

## **Layout Options**

| Content | Barcodes, alphanumerical text in all languages, dates, |
|---------|--|
|         | counters, shift codes, graphics, full Unicode support  |
|         | (see datasheet for MCX Software for more details)      |

### Interface

| interrace         |   |
|-------------------|---|
| Controller        | RJ45 socket   |
| I/O Interface box | D-SUB 15 HD female socket   |
| Power socket      | Power jack with screw lock  |
| Sensor            | Built-in sensor<br>External sensor can be connected directly to printer<br>or via I/O Interface box |
| Encoder           | 2 channel quadrature<br>Encoder can be connected directly to printer<br>or via I/O Interface box    |
| Beacon            | 4 output signals<br>Default use of 3 output lines to drive beacon lamps                             |
|                   |   |

# Mechanical

| Housing    | Anodised aluminium, black and natural |
|------------|---------------------------------------|
| Sole       | CrN treated aluminium                 |
| Dimensions | 121 (133) x 99 x 104.3 mm (LxWxH)     |
| Weight     | 0.89 kg (product only)                |



MCX printers are small, powerful printers ideal for coding and marking applications offering premium print quality at high speed.

MCX printers use HSAJET® smart card cartridges ensuring automatic detection of ink cartridges and adjustment of ink parameters for optimum print performance.

### **Electrical**

| Power        | 24 VDC   2.5A   60W    |
|--------------|------------------------|
| Power supply | 100-240 VAC   50-60 Hz |

## **Compliance and Regulations**

| Complies to       | CE, UKCA, RoHS, and EMC directives |
|-------------------|------------------------------------|
| Tariff no.        | 84714100                           |
| Country of origin | Denmark                            |

### In the box

| 22501010 | HSAJET MCX 1" Printer (2 pens) SC |
|----------|-----------------------------------|
| 72000120 | PSU AC/DC Adaptor 60W f/MCX, 24V  |

#### **Accessories**

| HSAJET MCX 4.3" Touch Controller   |
|--|
| HSAJET MCX 4.3" Touch Controller - panel mount   |
| MCX Software f/Windows w/dongle & usb stick  |
| HSAJET MCX I/O Interface Box   |
| Cable RJ45, CAT7 S/FTP, 1m, black  |
| Cable RJ45, CAT7 S/FTP, 3m, black  |
| Cable RJ45, CAT7 S/FTP, 5m, black  |
| Cable RJ45, CAT7 S/FTP, 10m, black   |
| Sensor, encoder, and beacon  |
| Large selection of brackets for installation on  |
| production lines (see accessories list)  |
| Large range of HSAJET® HP45si and HP45ai cartridges with smart card available in black, white, and various colours for most substrates (see other flyer) |
|  |

The information presented in this data sheet is obtained under specific conditions. No guarantee is given to the accuracy or correctness of the information. We reserve the right to make changes to functionalities of the product and the content of this data sheet without prior notification.